SUAVE: Painless Extension for an Object-Oriented VHDL

Peter J. Ashenden
University of Adelaide

Philip A. Wilsey, Dale E. Martin
University of Cincinnati

This work was partially supported by Wright Laboratory
under USAF contract F33615-95-C-1638.

SUAVE

SAVANT and
University of
Adelaide
VHDL
Extensions

Outline

- Design Objectives
- Extension to the type system
  - type derivation & inheritance
  - type extension
  - abstract types
  - class-wide types
- Extensions for encapsulation
  - private types and private parts
- Integrating encapsulation and inheritance

Design Objectives

- Support high-level modeling
  - improve encapsulation and information hiding
  - provide for hierarchies of abstraction
- Support re-use and incremental development
  - polymorphism, dynamic binding, type genericity
- Preserve capability for synthesis & other analysis
- Support hw/sw codesign
  - improved integration with programming languages

. . .

Design Objectives (cont)

- Refinement through elaboration of components
  - avoid repartitioning
- Preserve correctness of existing models
- Design principles from VHDL-93
  - preserve “conceptual integrity”

Overview of Extensions

- Borrow heavily from Ada-95
  - VHDL already has much in common with Ada
  - borrow encapsulation, information hiding, inheritance, genericity features
- Class-based *cf* programming by extension
  - class-based
    - replicates package features
    - choose one or the other, but not both!
  - programming by extension
    - integrates better with signal semantics

Type Derivation and Classes

- Adopt from Ada-95:
  - tagged records
  - type derivation
    - type derived from tagged record can add elements
    - inherits primitive operations from parent type
    - can override/augment operations
  - class-wide types, class-wide operations
    - T'Class is hierarchy of types derived from T
    - dynamic dispatching
  - abstract type and operations
- Signals and dynamic variables can be class-wide

Type Derivation Example

```
type instruction is
    tagged record
        opcode : opcode_type;
    end record instruction;

function privileged ( instr : instruction;  mode : protection_mode )
                    return boolean;

procedure disassemble ( instr : instruction;  file output : text );

type ALU_instruction is new instruction with
    record
        destination, source_1, source_2 : register_number;
    end record ALU_instruction;

procedure disassemble ( instr : ALU_instruction;  file output : text );
```

Type Derivation Example (cont)

```
type memory_instruction is abstract new instruction with record
        base : register_number;
        offset : integer;
    end record memory_instruction;

function effective_address_of ( instr : memory_instruction ) return natural;

procedure perform_memory_transfer ( instr : memory_instruction ) is abstract;

type load_instruction is new memory_instruction with record
        destination : reg_number;
    end record load_instruction;

procedure perform_memory_transfer ( instr : load_instruction );

type store_instruction is new memory_instruction with record
        source : reg_number;
    end record store_instruction;

procedure perform_memory_transfer ( instr : store_instruction );
```


Type Derivation Example (cont)

```
procedure execute ( instr : instruction'class ) is
begin
    disassemble ( instr, trace_file );
    if privileged(instr) and execution_mode = user then
        handle_privilege_violation;
    else
        . . .
    end if;
end procedure execute;
```

```
entity instruction_reg is
    port ( load_enable : in bit;
           instr_in : in instruction'class;
           instr_out : out instruction'class );
end entity instruction_reg;
```

Encapsulation

- Strengthen existing package feature
  - used to define secure ADTs
- Package can have *visible part* and *private part*
- *Private type*
  - declare *partial view* in visible part
    - includes some contractual details
  - declare *full view* in private part
- Allow packages in any declarative region
  - local ADTs

Encapsulation Example

```
package complex_numbers is
    type complex is private;
    constant i : complex;
    function cartesian_complex ( re, im : real ) return complex;
    function re ( C : complex ) return real;
    function im ( C : complex ) return real;
    function "abs" ( C : complex ) return real;
    function arg ( C : complex ) return real;
    function "+" ( L, R : complex ) return complex;
    function "–" ( L, R : complex ) return complex;
    . . .
private
    type complex is record
        re, im : real;
    end record complex;
end package complex_numbers;
```

Encapsulation Example (cont)

```
use complex_numbers.all;

signal a, b, sum : complex := cartesian_complex(0.0, 0.0);
signal enable : bit;
. . .
sum <= a + b after 10 ns when enable = '1' else
        0.0 + 0.0*i after 10 ns;
```


Interaction: Encapsulation and Derivation

- Adopt mechanisms from Ada-95
  - tagged private type
    - can be extended without revealing details of parent
  - private extension
    - concrete details of extension hidden
- See paper for example

Conclusion

- SUAVE improves VHDL's support for modeling
  - across the spectrum
    - system-level down to gate level
  - improves encapsulation, inheritance, genericity
  - integrates cleanly with existing language
- Full details in papers and TRs
  - http://www.ececs.uc.edu/~petera/suave.html
- Implementation in progress